#### YUTA BRASS VALVE

### 10 BAR LOCKABLE STRAIGHT VALVE







Size | 25 mm x 3/4"

PART	MATERIAL	
Body	Brass	
Ball	Brass	
Seat Ring	PTFE	
Bonnet	Brass	
Stem	Brass	
O - Ring	NBR	
Handle	Brass	
Cover	ABS	
Connection Nut	Brass	

### 10 BAR LOCKABLE STRAIGHT VALVE





Fig. LCBU-A

 Size: 1/2" x 3/4" Size: 3/4"x 1"

### MATERIALS

Locknut

PART	MATERIAL
Body	Brass
Ball	Brass
Seat Ring	PTFE
Bonnet	Brass
Stem	Brass
O - Ring	NBR
Handle	Brass
Cover	ABS
Coupling Nut	Brass
Gasket	SS304

### 10 BAR LOCKABLE MAGNETIC ANGLE VALVE





• 5ize 20 mm X 3/4" Size 25 mm X 3/4\*

### MATERIAIS

PART	MATERIAL
Body	Brass
3-Way Ball	Brass
Seat Ring	PTFE
Bonnet	Brass
Stem	Brass
O-Ring	NBR
Snap Ring	SS304
Hexagonal Nut	Brass
Rubber Washer	NBR
Compression Ring	Brass

#### YUTA BRASS VALVE

Fig. 901

Fig. 902

#### 10 BAR FLOATING ACTUATED THREADED VALVE



MATERIALS

PART	MATERIAL
Body	Brass
Ball	Stainless Steel

Size 901 | 1/2"-2.1/2" (Threaded Ends)

Size 902: 3" - 8" (Flanged Ends.)

ISO 9001 2L(US) SOLENOID VALVE

Working Pressure: Air, Water, Steam:0.1~1.5Mpa



### MATERIALS

PART	MATERIAL
Body	Brass
O - Ring	PTFE
Core Assembly	Iron
Magnetic Plate	lron:
Spring	Iron
Coil Assembly	Brass
Assembly of Piston	Aluminum
Cord Locks	Plastic
Name Plate	Aluminum
Gasket	Iron
Head Cover Nut	Iron

• Size: 1/2°-2"

### ISO 9001 2W(UW) SOLENOID VALVE

Working Pressure
Air: 0-0.7MPa Water: 0-0.5MPa Oil: 0-0.5MPa Steam: 0~7Mpa



• Size: 1/2' = 2"

# MATERIALS

PART	MATERIAL
Body	Brass
O - Ring	NBR
Core Assembly	Iron
Magnetic Plate	Iron
Spring	Iron
Coil Assembly	Brass
Coil Cover	Iron
Cord Locks	Iron
Name Plate	Aluminum
Gasket	Iron
Head Cover Nut	Iron





WWW.YUTA.CO.ID

Fig. GT

Non Rising Stem

Fig. BK Non Rising Stem

### 10 BAR GATE VALVE



Size : 1/2" = 4"

### MATERIALS

PART	MATERIAL	
Body	Brass	
Bonnet	Brass	
Disc	Brass	
Stem	Brass	
Packing	PTFE	
Handwheel	Cast Iron	

#### **Design Spesification**

\* Threaded Ends

### 10 BAR GLOBE VALVE



• Size: 1/2" - 4"

### MATERIALS

PART	MATERIAL	
Body	Brass	
Bonnet	Brass	
Disc	Brass	
Nut	Brass	
Stem	Brass	
Gasket	PTFE	
Handwheel	Cast Iron	

#### **Design Spesification**

\* Threaded Ends

### 25 BAR BALL VALVE

• Size 1/2" - 4"



Fig. FB

### MATERIALS

PART	MATERIAL	
Body	Brass	
Ball	Brass	
Seat Ring	PTFE	
Stem	Brass	
O - Ring	NBR	
Handwheel	Stainless Steel	

#### Design Spesification

\* Threaded Ends

#### **YUTA BRASS VALVE**

Fig. MFB

Fig. C

### 16 BAR BALL VALVE MALE TO FEMALE



• Size: 1/2"

### MATERIALS

PART	MATERIAL	
Body	Brass	
Ball	Brass	
Seat Ring	PTFE	
Stem	Brass	
Press Nut	Brass	
Handle	Aluminum	
(10104)C	Audilitati.	

#### **Design Spesification**

. Threaded Ends | Male - Female

### 10 BAR SWING CHECK VALVE



Size: 1/Z -4\*

### MATERIALS

PART	MATERIAL
Body	Brass
Hinge Pin	Brass
Disc	Brass
Cap	Brass

#### Design Spesification

• Threaded Ends

### 10 BAR SPRING CHECK VALVE



• Size Tt : 1/7 - 1"

 Size TS : 1 1/4" - 4" • Size ITS: 1/2" -4"

### MATERIALS

PART	MATERIAL
Body	Brass
Cap	Brass
Rod	ABS
Disk Gasket	NBR
Spring	Stainless Steel
Disc	ABS

#### Design Spesification

Threaded Ends

\* Filter : Stainless Steel 304

#### YUTA BRASS VALVE

### 10 BAR PLUG VALVE



• Size: 1/2" - 3/4"

Fig. MC

### MATERIALS

PART	MATERIAL	
Body	Brass	
Plug	Brass	
Washer	Brass	
Nut	Brass	
Locking	Brass	

#### **Design Spesification**

\* Threaded Ends

### 10 BAR LOCKABLE ANGLE VALVE



Size = 20 mm x 3/4°

. Size: 25 mm x 3/4"

## MATERIALS Fig. LCBP-A

MATERIAL Body Brass Brass PTFE Seat Ring Brass Bonnet Stem Brass NBR O - Ring Handle Brass Cover ABS Connection Nut Brass Ring SS304

### 10 BAR LOCKABLE ANGLE VALVE



◆ Size : 1/2"x 3/4"

. Size: 3/4"x 3/4"

## MATERIALS

Fig. LCB1 -A

